

# Data sheet



**sk-710.093**

**Bulky goods truck with supporting wheels**



**Outer dimensions:**

Width: 600 mm  
Depth: 400-1365 mm  
Height: 1700-920 mm  
Weight: 43,5 kg

Construction: steel, fixed welded, tiltable  
Colour: RAL 5010 gentian blue / powder-coated  
Load capacity: 550 kg

- \* Toe plate: 600 x 150 mm (W/D)
- \* incl. 4 pieces eyes, 60 x 20 mm
  - 2 pieces at a height of 600 mm
  - 2 pieces at a height of 1,600 mm
- \* incl. 2 fixed tension belts
- \* incl. 2 hooks per cross strut for fastening the tension belts when not in use
- \* with 2 pieces foldable, height-adjustable swivel castors as supporting wheels to reduce the clearance height
- supporting wheels of grey non-marking thermoplastic rubber tyres on plastic rim with precision deepgroove ball bearings, Ø 125 mm
- \* with brake lever acting on the polyurethane wheels
- \* 3 levels adjustable, dimensions when extended:
  - Pos. 1: 1,410 x 1,370 mm (D/H)
  - Pos. 2: 1,575 x 1,160 mm (D/H)
  - Pos. 3: 1,685 x 920 mm (D/H)
  - Dimensions with the heavy-duty truck upright: 600 x 1,700 mm (D/H)
- \* grip area with soft plastic grip cover black
- \* contact surface faced with grey hollow rubber profile and toe plate with vulcanized rubber

**Wheelset:** Ø 250 x 50 mm, polyurethane, non-marking  
deepgroove ball bearings

EAN-Nummer: 4035694074910  
Customs tariff no: 87168000  
Country of origin: European Community

**www.VARIOfit.eu**



# Data sheet



sk-710.093/AG

Bulky goods truck with supporting wheels, RAL 7016



12  
years  
warranty

## Outer dimensions:

Width:	600 mm
Depth:	400-1365 mm
Height:	1700-920 mm
Weight:	43,5 kg

Construction:	steel, fixed welded, tiltable
Colour:	RAL 7016 anthracite grey / powder-coated
Load capacity:	550 kg

- \* Toe plate: 600 x 150 mm (W/D)
- \* incl. 4 pieces eyes, 60 x 20 mm
  - 2 pieces at a height of 600 mm
  - 2 pieces at a height of 1,600 mm
- \* incl. 2 fixed tension belts
- \* incl. 2 hooks per cross strut for fastening the tension belts when not in use
- \* with 2 pieces foldable, height-adjustable swivel castors as supporting wheels to reduce the clearance height
- \* supporting wheels of grey non-marking thermoplastic rubber tyres on plastic rim with precision deepgroove ball bearings, Ø 125 mm
- \* with brake lever acting on the polyurethane wheels
- \* 3 levels adjustable, dimensions when extended:
  - Pos. 1: 1,410 x 1,370 mm (D/H)
  - Pos. 2: 1,575 x 1,160 mm (D/H)
  - Pos. 3: 1,685 x 920 mm (D/H)
  - Dimensions with the heavy-duty truck upright: 600 x 1,700 mm (D/H)
- \* grip area with soft plastic grip cover black
- \* contact surface faced with grey hollow rubber profile and toe plate with vulcanized rubber

---

**Wheelset:** Ø 250 x 50 mm, polyurethane, non-marking  
deepgroove ball bearings

---

EAN-Nummer: 4035694076259  
Customs tariff no: 87168000  
Country of origin: European Community

[www.VARIOfit.eu](http://www.VARIOfit.eu)

