

# Data sheet



sw-500.801

Push-handle dolly with tubular steel load surface



12  
years  
warranty

## **External dimensions:**

Width:	880 mm	Construction:	steel, screwed
Depth:	500 mm	Colour:	RAL 5010 gentian blue / powder-coated
Height:	880 mm	Weight:	9,5 kg
Handle height:	865 mm	Load capacity:	250 kg

## **Loading surface: (w/d)**

Material:	strut of tubular steel / powder-coated / RAL 5010 gentian blue
Bottom:	605 mm x 500 mm
Loading height:	185 mm

## **Wheelset:**

Ø 125 x 30 mm, thermoplastic rubber, grey, non-marking  
2 swivel castors with brakes and 2 fixed castors  
deepgroove ball bearings  
More safety with the VARIOfit® foot protection

EAN-No. 4035694001688  
Customs tariff no. 87168000  
Country of origin: European Community



# Data sheet



sw-500.801/AG

Push-handle dolly with tubular steel load surface, RAL 7016



## **External dimensions:**

Width:	880 mm	Construction:	steel, screwed
Depth:	500 mm	Colour:	RAL 7016 anthracite grey / powder-coated
Height:	880 mm	Weight:	9,5 kg
Handle height:	865 mm	Load capacity:	250 kg

## **Loading surface: (w/d)**

Material:	strut of tubular steel / powder-coated / RAL 7016 anthracite grey
Bottom:	605 mm x 500 mm
Loading height:	185 mm

## **Wheelset:**

Ø 125 x 30 mm, thermoplastic rubber, grey, non-marking  
2 swivel castors with brakes and 2 fixed castors  
deepgroove ball bearings  
More safety with the VARIOfit® foot protection

EAN-No. 4035694081628  
Customs tariff no. 87169090  
Country of origin: European Community

